

ATMs from the NH-1500 Series are our most popular retail models because they include plenty of state-of-the-art features at an affordable price. Plus, their small footprint and low weight makes them easy to fit into almost any location.

# **Features**

#### Reliability


Featuring exceptionally stable operation and advanced performance, the NH-1500 Series has a proven track record in the U.S. market.

# **Security**

This safe transaction environment includes a UL business-hour safe, PCI EPP (Encrypting PIN pad), and an optional electronic lock and KABA Mas Cencon safe lock.

# Capacity up to 4,000 Notes

Customize a dispenser profile up to 4,000 notes with the retail, free-standing NH-1500 Series. Flexible features allow us to design an ATM at a price range that can work for you.



Now offering the most complete line of financial and retail ATMs.



Compact yet powerful, the NH-1500 Series offers a great value for an ATM designed to handle high-traffic locations.

# **Dependable Customer Service**

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

# 

#### **Customer Display**

- 5.7" monochrome
- Optional 5.7" color LCD

#### Communication

- Dial-up
- Pre-dial (not supported by all processors)

#### Input Type

- 4 x 2 function keys
- 4 x 4 numeric keys
- PCI EPP (Encrypting PIN pad)

#### **Card Handling**

- Dip-type card reader
- Optional IC card reader (EMV)

#### **Supports Five Languages**

- English
- Spanish

#### **Cash Dispenser Options**

- 1,000-notes with removable cassette
- Optional 800-note drawer type (non-removable cassette)
- 2,000-note CDU can be upgraded to 2 cassettes for 4,000 notes

#### **Printers**

• 3.1" graphical thermal receipt printer

#### Security

- UL Business Hour safe
- Mechanical combination lock
- Optional KABA Mas Cencon safe lock
- Optional electronic lock

#### Miscellaneous

- Illuminated topper
- Voice guidance earphone jack

# **Power Supply**

• AC 110-230V, 50-60 Hz

#### **Operating Environment**

Temperature: 40°F–95°FHumidity: 15%–86%

### **Dimension and Weight**

Height: 55.4" (1,397 mm)Width: 16" (406 mm)Depth: 24" (610 mm)

• Weight: 269 lbs (122 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

